

SPIKES ROTORS

FARMGARD 

ERGON 120

80 - 120 HP

The Celli fixed-width spike rotor harrow has solid boron spikes at an angle that penetrates ground using minimal power. Because it was first designed for stony ground, the machine can take rough conditions. The tailgate traps soil, so it's released as a fine tilth. A suitable seedbed is often created in one pass.





Robust headstock



All gear side drive



Steel face to face rotor seals



Replaceable boron steel spikes



Multi position tailgate



Heavy duty gearbox



Features:

- Exceptional design rotor for one pass in primary conditions
- Multi flange waterproof sealing system exclusive to Celli to give rotor bearings full protection from water, dirt, wire and other foreign material
- Two piece tailgates for large range of seedbed finishes
- Steel face-to-face rotor seals for longer lasting rotor bearings
- Efficient multi speed gearboxes to minimise power loss and heat build-up
- Robust headstock for a stronger, longer lasting machine
- Box section body for rigidity and long life
- Oil filled rotor bearings for low maintenance and guaranteed lubrication
- Four speed gearbox rated up to 120 hp
- Swinging lower links
- Gear side drive
- 170mm replaceable boron steel spikes
- 250mm working depth
- Slip clutch



OPTIONS:

- Cage Roller
- Packer Roller
- Cam clutch
- Hydraulic adjustment for rear roller



	cm	cm	HP	kg*	Nr
ERGON 120 F 205	232	205	75 - 120	1080	40
ERGON 120 F 230	257	230	80 - 120	1160	45
ERGON 120 F 255	282	255	85 - 120	1240	50
ERGON 120 F 280	307	280	90 - 120	1300	55
ERGON 120 F 305	332	305	100 - 120	1380	60

*weight includes packer roller



CALL FARMGARD 24 HOURS
0800 FARMGARD



EMAIL US FOR MORE INFO
sales@farmgard.co.nz



DOWNLOAD A FREE INFO PACK OR BROCHURE
farmgard.co.nz