

TWIN AUGER

20m³

The 20m³ twin vertical auger mixer wagon is ideal for operators who want more capacity without extra height, while maintaining quality and heavy-duty construction. Despite the extra capacity, the VF2000 is a compact unit, and ideal for chopping high density material. The unique HDM augers are designed to allow quick chopping of dry material or large bales.





Independent chassis to allow for large torque loading



20mm floor for extra strength



Rolled walls for superior mixing



Electric in cab control box



1m wide feed door for even feeding



Slat and chain elevator, low maintenance



OPTIONS:

Front elevator and platform (shown above)
 PVC side elevator
 Cable controlled gearbox changeover
 Auger magnets
 Fibre knives
 Hydraulic counter knives
 22mm augers
 Hardox wear plates
 Chromium-carbide coated knives
 Hardox wall liner



ABBEY
 MACHINERY
 since 1947

Specifications:

- 20m3 capacity (19m3 to top of tub, 23m3 to top of rubber extension)
- Twin vertical auger with 7 manganese boron knives per auger
- Single axle with 435/50 x 19.5 flotation tyres
- Right and left side discharge doors
- 560mm long slat and chain discharge elevator (mounted on RH door)
- Electric in cab control box for all functions (1 DA hyd bank required)
- Large counter knives
- Electronic scales with cover over scales
- 4 weigh bars on independant chassis
- Hydraulic brakes
- LED rear lights
- Wide angle PTO shaft with shearbolt protection
- Two speed gearbox with manual changeover handle
- Comer SOM planetary gearboxes, with 3-year warranty
- Rubber top extension
- 3 stage HD winding jack
- Galv ladder mounted on LHS
- 15mm auger flighting
- 8mm ST 52 hardox wall
- 1 year warranty

| Overall height | Overall height without rubber extension | Overall length | Unladen weight |
|----------------------------------|---|------------------------|---------------------|
| 3000mm | 2760mm | 7000mm | 7500kgs |
| Overall width with elevator open | Distance from wheel to edge of elevator | Tub height | Tub base to ground |
| 3145mm | 640mm | 2060mm | 960mm |
| Discharge height (elevator down) | Turning circle (hitch to wheel) | Tub top opening length | Overall wheel width |
| 800mm | 4680mm | 5100mm | 2250mm |



CALL FARMGARD 24 HOURS
0800 FARMGARD



EMAIL US FOR MORE INFO
sales@farmgard.co.nz



DOWNLOAD A FREE INFO PACK OR BROCHURE
farmgard.co.nz