

TWIN AUGER

15m³

The 15m³ twin vertical auger mixer wagon is ideal for operators who want more capacity without extra height, while maintaining quality and heavy-duty construction. Despite the extra capacity, the VF1500 is a compact unit, and ideal for loading with small tractors.



* shown with optional super single tyres



Independent chassis to allow for large torque loading



20mm floor for extra strength



Rolled walls for superior mixing



Electric in cab control box



1m wide feed door for even feeding



Slat and chain elevator, low maintenance



Specifications:

- 15m3 capacity
- Twin vertical auger with 5 manganese boron knives per auger
- Twin 235/75 R 17.5 tyres
- Right and left side discharge doors
- 560mm long slat and chain discharge elevator (mounted on RH door)
- Electric in cab control box for all functions (1 DA hyd bank required)
- Large counter knives
- Electronic scales with cover over scales
- 4 weigh bars on independant chassis
- Hydraulic brakes
- LED rear lights
- Wide angle PTO shaft with shearbolt protection
- Comer SOM planetary gearboxes, with 3-year warranty
- Raised top retaining ring
- 3 stage HD winding jack
- Galv ladder mounted on LHS
- 15mm auger flighting
- 6mm ST 52 wall
- 1 year warranty



OPTIONS:

- PVC side elevator
- Auger magnets
- Fibre knives
- Hydraulic counter knives
- Wear plates
- Chromium-carbide coated knives
- Hardox wall liner
- 435/50 x 19.5 super single tyres (raises height by 150mm)

Overall height	Overall height without top ring	Overall length	Unladen weight
2650mm	2490mm	6400mm	5780kgs
Overall width with elevator open	Distance from wheel to edge of elevator	Tub height	Tub base to ground
2900mm	600mm	1620mm	830mm
Discharge height (elevator down)	Turning circle (hitch to wheel)	Tub top opening length	Overall wheel width
660mm	4500mm	4915mm	2200mm



CALL FARMGARD 24 HOURS
0800 FARMGARD



EMAIL US FOR MORE INFO
sales@farmgard.co.nz



DOWNLOAD A FREE INFO PACK OR BROCHURE
farmgard.co.nz